

# CT Series

# CT Series

The CT series is a multi-functional Touch system designed specifically for retail & hospitality applications such as hotels, restaurants and shops.


- ❑ Cost effective stand alone all-in-one POS terminal
- ❑ 15" and 17" LCD with Touch screen
- ❑ Extremely solid and reliable structure
- ❑ OSD and power switch control panel on the rear
- ❑ Removable HDD Design easy for maintenance
- ❑ Available with different touch panel technology (5-wire resistive, SAW and Capacitive)
- ❑ Water spill resist from the front bezel side
- ❑ Hidden Connector and Power Cable Design
- ❑ Intel Core 2 Duo to Celeron High Performance Platform



Tilt Angle 0°~ 90°: Adapt to operation in any environment



Triple Track Magnetic Stripe Reader for membership management or operator identification



Removable Base and Wall Mounting capability with 75mm VESA holes



Second Display can be integrated to the back side of the system.



Customer Display VFD type (2X20) VFD Customer Display can be integrated to the back side of the system



Easily arrange the cables inside the stand.



# CT Series

The Best Touch Solution



CT-150/CT-170

Specification		MODEL	CT-150	CT-170
Motherboard	CPU Type	Intel Core2 Duo, Core2 Quad, Pentium Dual-Core, Celeron Dual-Core, or Celeron 4xx processor (Socket 775)		
	System Freq.	800/1066/1333/1600 MHz		
	Memory	Two 240-PIN DDRII DIMM up to 4GB Max. (Support DDRII 667/800 and Dual Channel Mode)		
	Video	Integrated GMA3100 with Max. 256MB Shared Video Memory		
	Ethernet	Onboard 10/100Mbps Ethernet		
	Audio	AC97 Codec Audio Subsystem		
Device	HDD	2.5" or 3.5" IDE/SATA x 1 (Support Ultra DMA 100)	2.5" IDE/SATA x 1 (Support Ultra DMA 100)	
I/O Connector	Serial Port x 1 + 2 (Optional) Parallel Port x 1 USB 2.0 Port x 4 (External) + 4 (Internal) PS/2 Mini-DIN Keyboard Port x 1 PS/2 Mini-DIN Mouse Port x 1 RJ-45 Ethernet Port x 1 Audio Line-in / Line-out / Mic-in Jack x 1 Set <small># Available Serial &amp; USB port may be different according to interface of touch panel and integrated optional devices.</small>			
Monitor	15" XGA TFT LCD		17" SXGA TFT LCD	
Touch Screen	TW 5-wire or ELO Resistive Touch Screen (RS-232 or USB Interface)			
Power Supply	Internal Power Supply			
Dimension (mm)	378(W) x 226(D) x 348(H)		418(W) x 241(D) x 357(H)	
Optional Integrated Device	VFD Customer Display, MSR Card Reader, Fingerprint Scanner 3-in-1 MSR + Smartcard + i-Button Reader			

# Above specification may change without advance notice.