

FT Series

FT Series

The fanfree system is designed for application in quiet environments. Housed with stylish aluminum main unit casing which will add a fashionable spotlight to your counter while providing effective ventilation for quiet operation.

- ❑ Compact All-in-one M/B design with Rich I/O especially for POS Terminal
- ❑ Low power consumption and fanfree design for quiet operation
- ❑ VIA C7 Mobile or Intel Mobile High Performance Platform
- ❑ Good Flexibility Design suitable for various applications
- ❑ Available with different Touch Panel Technology (5-wire resistive, SAW, Capacitive)
- ❑ Extremely Solid and Reliable structure
- ❑ Water spill resist from the front bezel side
- ❑ Power Switch and LCD Brightness Control Panel on the Side
- ❑ Hidden Connector and Power Cable Design
- ❑ Optional Wi-Fi Wireless LAN for data transmission
- ❑ Optional CF Socket functionality for thin client application
- ❑ Removable HDD Design for easy maintenance



Tilt Angle 0°~ 90°: Adapt to operation in any environment



Triple Track Magnetic Stripe Reader for membership management or operator identification

Removable Base and Wall Mounting capability with 75mm VESA holes



Second Display can be integrated to the back side of the system.



Customer Display VFD type (2X20) VFD Customer Display can be integrated to the back side of the system



Easily arrange the cables inside the stand.

FT Series

The Best Fanless Touch Solution



FT-150/FT-170



Specification		MODEL	FT-150	FT-170
Motherboard	CPU		VIA C7-M 1.6GHZ CPU (Options: Intel Pentium M and Celeron M Processor)	
	System Freq.		400/ 533 MHz	
	Chipset		VIA CN700 + VT8237R-PLUS (Intel 910GMLE+ICH6-M)	
	Memory		One 240PIN DDR2 DIMM socket up to 1GB (Two 200-PIN DDR2 400 SO-DIMM Slots up to 2GB)	
	Video		Integrated Graphic Engine	
	Ethernet		10/100Mbps Ethernet	
	Audio		AC97 Audio Codec	
Storage Device			2.5" or 3.5" IDE/SATA HDD x 1 Compact Flash II Socket x 1	
I/O Connector			Serial Port x 4 Parallel Port x 1 USB 2.0 Port x 4 PS/2 Mini-DIN Keyboard Port x 1 & Mouse Port x 1 VGA Port x 1 (for second screen) RJ-45 Ethernet Port x 1 RJ-12 Cash Drawer Port x 2 Audio Line-out Port x 1 & Mic-in Port x 1	
Expansion Slot			Mini PCI Slot x 1	
Monitor			15" XGA TFT LCD	17" SXGA TFT LCD
Touch Screen			TW 5-wire or ELO Resistive Touch Screen (RS-232 or USB Interface)	
Power Supply			External Power Supply	
Dimension (mm)			380(W) x 255(D)x 312(H)	418(W) x 254(D)x 328(H)
Optical Integrated Device			VFD Customer Display, MSR Card Reader, Fingerprint Scanner, 3-in-1 Hybrid Card Reader, Second 12"/15"/17" LCD Screen with or without Touch Screen	