

RCT Series

The Best Touch Solution



Specification		MODEL	RCT-150
Motherboard	CPU Type	Intel Core2 Duo / Intel Pentium Dual-Core and / Celeron Dual-Core processor	
	System Freq.	1066/800 MHZ System Bus (up to 65W TDP)	
	Chipset	Intel G41 + ICH7	
	Memory	Two DDRIII DIMM socket (240PIN DDRIII 800/667 up to 4GB)	Two DDRII SO-DIMM socket (200PIN DDRII 800/667 up to 4GB)
	Video	Integrated GMAx4500 Graphic Engine	
	Ethernet	Realtek 888VC audio	Realtek ALC662 audio
	Audio	Onboard 10/100/1000Mbps	Onboard 10/100/1000Mbps
Storage Device		2.5" SATA HDD x 1	2.5" SATA HDD x 1 Compact Flash II Socket x 1
I/O Connector		Serial Port x 1+ 2(Optional) Parallel Port x 1 DVI-D Port x 1 USB 2.0 Port x 4 External +4 Internal PS/2 Mini-DIN Keyboard Port x 1 PS/2 Mini-DIN Mouse Port x 1 RJ-45 Ethernet Port x 1 Audio Line-out Port x 1 & Line-in Port x 1 & Mic-in Port x 1 <small>#Available Serial & USB port may be different according to interface of touch panel and integrated optional devices.</small>	Serial Port x 3 External + 1 Internal Parallel Port x 1 USB 2.0 Port x 4 External +4 Internal PS/2 Mini-DIN Keyboard Port x 1 PS/2 Mini-DIN Mouse Port x 1 RJ-45 Ethernet Port x 1 <small>#Available Serial & USB port may be different according to interface of touch panel and integrated optional devices.</small>
Expansion Slot		One PCI bus connector	
Monitor		15" XGA TFT LCD	
Touch Screen		5-wire Resistive Touch Panel (Optional: Capacitive, SAW and IR touch panel)	
Power Supply		Internal Power Supply	
Dimension (mm)		380(W)x217(D)x311(H)	
Optional Integrated Device		VFD Customer Display, MSR Card Reader, Fingerprint Scanner 3-in-1 MSR+Smartcard+i-Button Reader Second LCD Screen with or without Touch Screen	

Above specification may change without advance notice.