



R180II THERMAL PRINTER

R180II

Thermal Printer

Setting the standard for value-class thermal receipt printers, TEAMSable delivers an affordable POS printer that provides all popular connection interfaces, including USB, Serial and Ethernet, with state-of-the-art speed and best-in-class reliability.

R180II Key Features at a Glance:

- Serial, USB and Ethernet Built-In
- Programmable Paper Saving Options
- Auto-Cutter – Selectable Full or Partial Cut
- Drop and Print Paper Loading
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches – Intuitive Keypad Programming
- Supports Asian Character Sets with Standard Memory
- Includes Starter Paper Roll, External Power Adapter and Cord, Paper Width Selector, Quick Reference Manual, Serial Cable & USB Cable



Slim
Fanless Design



Cable-Free
Management



Integrated MSR
(Optional)



Integrated Scanner
(Optional)



www.teamsable.com

1911 Hartog Dr. San Jose, CA 95131



1-408-452-8788



sales@searching

R180II

- Fast 230mm/Second Print Speed
- Simple Drop-In Paper Loading
- Standard Auto Paper Cutter
- Includes Cables and Power Supply
- Compatible with Most Popular POS Software Applications
- SDK Available for IOS and Android Operating Systems

R180II	
Hardware	
Max. Print Speed	230mm per Second
Printing Method	Direct Thermal
Resolution	180 DPI x 180 DPI
Paper Roll Width Paper Maximum Diameter Paper Thickness	82 / 80 / 76 / 69 / 57mm ± 0.5mm 83mm 0.06mm ~ 0.08mm
Auto Paper Cutting Method	Auto-Cutter with Selectable Full or Partial Cut
Bar Code –1D 2D	UPC-A / UPC-E / EAN8 / EAN13 / Code39 / Code93 / CODE128 / CODABAR / ITF PDF417 / QR Code / Maxicode / GS1
Interface	Serial + USB + Ethernet
Drawer Port	Up to 2 Drawers (+24VDC)/Drawer Compulsion
Power Supply	AC 100 ~ 240 V, 50/60 Hz Adapter Included
Current/Power Usage	1.5A / 36W
Operating Temperature	40° ~ 114°F (5° ~ 45°C)
Operating Humidity	20% ~ 90% RH (Non-Condensing)
Software	
Interpreter	ESC/POSTM
Support OS	Windows XP Prof./XP Home/2000 Server/2000 Professional/POSReady 2009 (32 bit) Windows XP (64bit) Window 10/8.1/8/7/Server 2012/Server 2008/Server 2003/Vista (32 bit and 64 bit) Linux /OPOS/JavaPOS Windows/Java POS Linux (Other) iOS / Android (Software Development Kit)
Packaging	
Dimensions	5-3/4"W x 5-9/16"H x 7-11/16"D
Ship Weight	6 lbs
Certification	
Safety and EMI	FCC / RoHS