



15N-RM-DSANDROID DIGITAL
SIGNAGE

15N-RM-DS

15" Android Digital Signage

TEAMSable 15N-RM-DS All-In-One Digital Signage solution powered by Android, gives your business the ability and flexibility to deploy your advertising and promotional content quickly and easily to your audience and customers. With Digital Signage, you can continuously rotate messaging and deliver them in a more interactive and engaging way with digital content that will improve customer experience and return on investment.

FEATURES:

- 15.6" LCD Panel Display
- 1920 x 1080 Resolution
- · Cortex-A17, Quad Core CPU
- · 2GB DDR3L Memory
- 8/16GB eMMC Storage, SD card (x1)
- 10 point capacitive Touch Screen
- Android 9.0



10-POINT CAPACITIVE TOUCHSCREEN



HIGH-PERFORMANCE CPU & OS



SLIM DESIGN









15N-RM-DS DIGITAL SIGNAGE

15N-RM-DS	
	Hardware
Display	15.6" (16:9 Diagonal) TFT LCD, LVDS
Resolution	1920 RGB (H) x 1080 (V)
Touch Technology	10 Point Capacitive
CPU	Cortex A17, QuadCore 1.6GHz
Memory	2GB DDR3L
Internal Storage	8GB eMMC (up to 16GB)
Power Supply	12V/5A Adapter
OS Support	Android 9.0 Pie
Wireless Communication	WiFi: IEEE 802.11a/b/g/n, Bluetooth 4.0
Ethernet Communication	RJ45: 10/100/1000 Mbps LAN, Power Over Ethernet (Optional)
Media Format Support	Video: MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV
	Audio: MP2, WMA, WAV, AAC, OGG, ASF
	Picture: JPG, BMP, GIF
	External Ports
USB	USB 2.0 Type-A x 1
Micro USB	Micro USB 2.0 x 1
SD Card Slot	SD Card (SDHC Class10 compatible) x 1
Peripheral Port	Peripheral Port x 3
GPIO Port	GPIO x 2
Ethernet	RJ45 with 5V/12V x 2
DC Adapter Slot	12V/5A x 1
Audio	3.5mm Jack x 1, S/PDIF x 1
Speaker	Stereo Speaker: 3W × 2, Amplifier: 1.25W x 2
Mount	VESA 100x100mm
	Environment
Operating Temperature	0°C – 40°C (32° – 104°F)
Storage Temperature	-10°C – 55°C (14°F – 131°F)
Relative Humidity	10% – 90% (Non-Condensing)
	Packaging
Dimension	1" (L) x 5.2" (W) x 9.4" (H) inches)
Weight	0.9 kg (2.1 lbs)